NSN 5340-01-370-2348

Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-370-2348

Thread Class:

2b left internal (includes through thread)

Thread Direction:

Right-hand left internal (includes through thread)

Thread Length:

0.438 inches left internal (includes through thread)

Hole Diameter:

Between 0.148 inches and 0.153 inches

Length:

Between 0.433 inches and 0.453 inches

Cross-sectional Shape:

Hexagon

Width Across Flats:

Between 0.244 inches and 0.256 inches

Thready Qty Per Inch (tpi):

32 left internal (includes through thread)

Thread Size:

0.1380 inches left internal (includes through thread)

Right Projection Diameter:

Between 0.186 inches and 0.191 inches

Right Projection Length:

Between 0.162 inches and 0.168 inches

Material:

Steel comp 303 or steel comp 203ez

Material Specification:

Astm a582 assn standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Style Designator:

Projection one end left internal thread

Thread Series Designator:

Unc left internal (includes through thread)

Specification Data:

80205-nas1830 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5340-01-370-2348

Spacing Threaded Standoff - Page 2 of 2

Fiig: A08900

