

View Online at <https://aerobasegroup.com/nsn/5340-01-370-5568>

Thread Pitch Diameters:

+2.675 to 2.775 millimeters left internal (includes through thread)+2.580/+2.655 millimeters right external

Thread Direction:

Right-hand left internal (includes through thread)right-hand right external

Thread Length:

5.0 millimeters left internal (includes through thread)4.25 millimeters and 4.75 millimeters right external

Length:

Between 17.25 millimeters and 17.75 millimeters

Cross-sectional Shape:

Hexagon

Width Across Flats:

6.35 millimeters

Thread Size:

2.927 millimeters left internal (includes through thread)2.927 millimeters right external

Thread Pitch In Millimeters:

0.5 left internal (includes through thread)0.5 right external

Thread Tolerance Class:

6h internal left internal (includes through thread)6g external right external

Right Projection Diameter:

2.927 millimeters

Right Projection Length:

Between 4.25 millimeters and 4.75 millimeters

Special Features:

Includes nylon locking element on external threads

Material:

Steel comp 303 standoff

Material Specification:

Qq-s-764 cond a federal specification single material response standoff

Surface Treatment:

Passivate standoff

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response standoff

Style Designator:

Left internal and right external thread

Thread Series Designator:

M left internal (includes through thread)m right external

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A08900