## NSN 5340-01-371-3159

Spacing Threaded Standoff - Page 1 of 2

**AeroBase** Group

View Online at https://aerobasegroup.com/nsn/5340-01-371-3159

**Thread Class:** 

2b left internal (includes through thread)

**Thread Direction:** 

Right-hand left internal (includes through thread)

Thread Length:

0.745 inches and 0.755 inches left internal (includes through thread)

**Hole Diameter:** 

Between 0.148 inches and 0.153 inches

Diameter:

Between 0.244 inches and 0.256 inches

Length:

Between 0.745 inches and 0.755 inches

**Cross-sectional Shape:** 

Round

Thready Qty Per Inch (tpi):

40 left internal (includes through thread)

**Thread Size:** 

0.1120 inches left internal (includes through thread)

**Right Projection Diameter:** 

Between 0.185 inches and 0.188 inches

**Right Projection Length:** 

Between 0.102 inches and 0.108 inches

Material:

Steel comp 303se or steel comp 203ez

**Material Specification:** 

Astm a582 assn standard all material responses

**Surface Treatment:** 

Passivate

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

Style Designator:

Projection one end left internal thread

**Thread Series Designator:** 

Unc left internal (includes through thread)

**Specification Data:** 

80205-nas1830 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

**Demilitarization:** 

No

## NSN 5340-01-371-3159

Spacing Threaded Standoff - Page 2 of 2



Fiig:

A08900