

View Online at <https://aerobasegroup.com/nsn/5340-01-371-4752>

Mounting Hole Type:

Plain and threaded

First Leg Length:

2.250 inches

Second Leg Length:

3.880 inches

Second Leg Width:

4.000 inches

Second Leg End Width:

0.750 inches

First Leg Hole Diameter:

0.437 inches

Second Leg Hole Diameter:

0.312 inches

Second Leg Distance From Edge To Hole Center Along Width:

37.500 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.630 inches

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

4.000 inches

First Leg Distance Between Hole Centers Along Width:

3.380 inches

First Leg Distance From Edge To Hole Center Along Width:

0.620 inches

First Leg Distance From Edge To Hole Center Along Length:

1.130 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square and tapered

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

5/16-18unc02b threads for the one mtg hole in second leg; dwg name-axle disconnect control bracket; prime law mil-p-53030 or mil-p-52192

Material:

Steel

Material Specification:

Astm a36 assn standard single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-53039 military specification single treatment response or mil-c-46168 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-53039 spec.