

View Online at <https://aerobasegroup.com/nsn/5340-01-371-4752>

**Mounting Hole Type:**

Plain and threaded

**First Leg Length:**

2.250 inches

**Second Leg Length:**

3.880 inches

**Second Leg Width:**

4.000 inches

**Second Leg End Width:**

0.750 inches

**First Leg Hole Diameter:**

0.437 inches

**Second Leg Hole Diameter:**

0.312 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

37.500 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.630 inches

**First Leg Thickness:**

0.250 inches

**Second Leg Thickness:**

0.250 inches

**First Leg Width:**

4.000 inches

**First Leg Distance Between Hole Centers Along Width:**

3.380 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.620 inches

**First Leg Distance From Edge To Hole Center Along Length:**

1.130 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square and tapered

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

5/16-18unc02b threads for the one mtg hole in second leg; dwg name-axle disconnect control bracket; prime law mil-p-53030 or mil-p-52192

**Material:**

Steel

**Material Specification:**

Astm a36 assn standard single material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-53039 military specification single treatment response or mil-c-46168 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-53039 spec.