

View Online at <https://aerobasegroup.com/nsn/5340-01-372-9954>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.500 inches

**Second Leg Length:**

1.380 inches

**Second Leg Width:**

2.190 inches

**First Leg Hole Diameter:**

0.171 inches

**Second Leg Hole Diameter:**

0.171 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.812 inches

**Second Leg Distance Between Hole Centers Along Length:**

0.875 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.190 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.225 inches

**First Leg Thickness:**

0.060 inches

**Second Leg Thickness:**

0.060 inches

**First Leg Width:**

2.190 inches

**First Leg Distance Between Hole Centers Along Width:**

1.063 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.560 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Cut out

**Second Leg Hole Arrangement Style:**

Four holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Cutout Length:**

0.880 inches

**Second Leg Cutout Width:**

1.430 inches

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 h32 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 cl 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.