NSN 5340-01-374-1923

Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-374-1923

Th	read	I C	lass:

2b left internal (includes through thread)2a right external

Thread Direction:

Right-hand left internal (includes through thread)right-hand right external

Thread Length:

0.217 inches left internal (includes through thread)0.148 inches right external

Length:

Between 0.295 inches and 0.299 inches

Cross-sectional Shape:

Hexagon

Width Across Flats:

0.157 inches

Thready Qty Per Inch (tpi):

48 left internal (includes through thread)48 right external

0.099 inches left internal (includes through thread)0.099 inches right external

Right Projection Diameter:

0.099 inches

Right Projection Length:

Between 0.181 inches and 0.193 inches

Material:

Steel comp 303

Material Specification:

Astma582 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072 e300 military specification single treatment response

Style Designator:

Left internal and right external thread

Thread Series Designator:

Unc left internal (includes through thread)unc right external

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A08900

Mil-std (military Standard):

Mil-f-14072 spec.