## NSN 5340-01-374-4540

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-374-4540

Mounting Hole Diameter:
0.406 inches
First Leg Length:
5.950 inches
Second Leg Length:
6.340 inches
Second Leg Width:
2.910 inches
Second Leg Corner Radius:
0.500 inches
First Leg Hole Diameter:
0.250 inches
Second Leg Hole Diameter:
0.250 inches
Second Leg Distance Between Hole Centers Along Width:
5.000 inches
Second Leg Distance From Edge To Hole Center Along Width:
0.500 inches
Second Leg Distance From Edge To Hole Center Along Length:
0.500 inches
First Leg Thickness:
0.250 inches
Second Leg Thickness:
0.250 inches
Center Section Height:
4.620 inches
Center Section Width:
2.000 inches
Center Section Thickness:
0.250 inches
First Leg Width:
1.000 inches
First Leg Distance Between Hole Centers Along Width:
3.950 inches
First Leg Distance From Edge To Hole Center Along Width:
0.500 inches
First Leg Distance From Edge To Hole Center Along Length:
0.500 inches
First Leg End Radius:
0.500 inches
First Lea Style:

End radius

## NSN 5340-01-374-4540

Double Angle Bracket - Page 2 of 2



First Leg Hole Arrangement Style:
Two holes
Second Leg Style:
Corner radius
Second Leg Hole Arrangement Style:
Two holes
Second Leg Relationship To First Leg:
Not identical
First Leg Angle:
90.0 degrees
Second Leg Angle:
90.0 degrees
Material:
Steel
Material Specification:
Astma36 assn standard single material response
Surface Treatment:
Phosphate zinc
Surface Treatment Specification:
Mil-std-171 5.1.1 military specification single treatment response
Style Designator:
Double angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-std-171 spec.