NSN 5340-01-374-4540

Double Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-374-4540

| Mounting Hole Diameter: |
|--|
| 0.406 inches |
| First Leg Length: |
| 5.950 inches |
| Second Leg Length: |
| 6.340 inches |
| Second Leg Width: |
| 2.910 inches |
| Second Leg Corner Radius: |
| 0.500 inches |
| First Leg Hole Diameter: |
| 0.250 inches |
| Second Leg Hole Diameter: |
| 0.250 inches |
| Second Leg Distance Between Hole Centers Along Width: |
| 5.000 inches |
| Second Leg Distance From Edge To Hole Center Along Width: |
| 0.500 inches |
| Second Leg Distance From Edge To Hole Center Along Length: |
| 0.500 inches |
| First Leg Thickness: |
| 0.250 inches |
| Second Leg Thickness: |
| 0.250 inches |
| Center Section Height: |
| 4.620 inches |
| Center Section Width: |
| 2.000 inches |
| Center Section Thickness: |
| 0.250 inches |
| First Leg Width: |
| 1.000 inches |
| First Leg Distance Between Hole Centers Along Width: |
| 3.950 inches |
| First Leg Distance From Edge To Hole Center Along Width: |
| 0.500 inches |
| First Leg Distance From Edge To Hole Center Along Length: |
| 0.500 inches |
| First Leg End Radius: |
| 0.500 inches |
| First Lea Style: |

End radius

NSN 5340-01-374-4540

Double Angle Bracket - Page 2 of 2



| First Leg Hole Arrangement Style: |
|--|
| Two holes |
| Second Leg Style: |
| Corner radius |
| Second Leg Hole Arrangement Style: |
| Two holes |
| Second Leg Relationship To First Leg: |
| Not identical |
| First Leg Angle: |
| 90.0 degrees |
| Second Leg Angle: |
| 90.0 degrees |
| Material: |
| Steel |
| Material Specification: |
| Astma36 assn standard single material response |
| Surface Treatment: |
| Phosphate zinc |
| Surface Treatment Specification: |
| Mil-std-171 5.1.1 military specification single treatment response |
| Style Designator: |
| Double angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A042a0 |
| Mil-std (military Standard): |
| Mil-std-171 spec. |
| |