NSN 5340-01-374-5508

Spacing Threaded Standoff - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5340-01-374-5508 |
|--|
| Thread Class: |
| 3b left internal (includes through thread) |
| Thread Direction: |
| Right-hand left internal (includes through thread) |
| Thread Length: |
| 0.420 inches left internal (includes through thread) |
| Diameter: |
| Between 0.320 inches and 0.321 inches |
| Length: |
| 0.700 inches |
| Cross-sectional Shape: |
| Round |
| Thready Qty Per Inch (tpi): |
| 32 left internal (includes through thread) |
| Thread Size: |
| 0.190 inches left internal (includes through thread) |
| Special Features: |
| Oval head with 2 mounting holes on unthd end 0.097 in. Min and 0.102 in. Maximum dia; insert provides thds |
| Material: |
| Aluminum alloy 6061 standoffsteel comp 304 insert |
| Material Specification: |
| Mil-a-12545 military specification single material response standoff |
| Surface Treatment: |
| Chromate standoff |
| Surface Treatment Specification: |
| Mil-c-5541 military specification single treatment response standoff |
| Style Designator: |
| Left internal thread |
| Thread Series Designator: |
| Unf left internal (includes through thread) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A08900 |
| Mil-std (military Standard): |

Mil-a-12545 spec.