NSN 5340-01-375-7254

Spacing Threaded Standoff - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5340-01-375-7254 |
|---|
| Thread Class: |
| 2a left internal (includes through thread)2a right internal |
| Thread Direction: |
| Right-hand left internal (includes through thread)right-hand right internal |
| Thread Length: |
| 1.000 inches left internal (includes through thread)1.000 inches right internal |
| Diameter: |
| 0.250 inches |
| Length: |
| 2.375 inches |
| Cross-sectional Shape: |
| Round |
| Thready Qty Per Inch (tpi): |
| 32 left internal (includes through thread)32 right internal |
| Thread Size: |
| 0.164 inches left internal (includes through thread)0.164 inches right internal |
| Material: |
| Stainless steel |
| Material Specification: |
| Astm-a-581 assn standard single material response and astm-a-582 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Mil-f-14072c military specification single treatment response |
| Style Designator: |
| Left internal and right internal threads |
| Thread Series Designator: |
| Unc left internal (includes through thread)unc right internal |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A08900 |
| Mil-std (military Standard): |

Mil-f-14072c spec.