## NSN 5340-01-376-3121

Loop Clamp - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-376-3121

| Tongue Hole Type: Round, threaded  Cushioning Environmental Protection: Fuel resistant and oil resistant  Overall Width: 0.830 inches  Center To Center Distance Between Loop And Mounting Hole: 2.330 inches  Loop Inside Diameter: 0.960 inches  Special Features:  Clamp is hinged with two attached brackets, four moubting holes; clamp loop has 3 holes to support oil lines; 2 holes 0.8 0.960 in. Dia., clamp secured together by one screw.  Material:  Stainless steel bandrubber butadiene nitrile cushion  Style Designator:  Hinged & center mtd  Shelf Life: |                    |
|--|--------------------|
| Cushioning Environmental Protection: Fuel resistant and oil resistant  Overall Width:  0.830 inches  Center To Center Distance Between Loop And Mounting Hole:  2.330 inches  Loop Inside Diameter:  0.960 inches  Special Features:  Clamp is hinged with two attached brackets, four moubting holes; clamp loop has 3 holes to support oil lines; 2 holes 0.8 0.960 in. Dia., clamp secured together by one screw.  Material:  Stainless steel bandrubber butadiene nitrile cushion  Style Designator:  Hinged & center mtd  |                    |
| Fuel resistant and oil resistant  Overall Width:  0.830 inches  Center To Center Distance Between Loop And Mounting Hole:  2.330 inches  Loop Inside Diameter:  0.960 inches  Special Features:  Clamp is hinged with two attached brackets, four moubting holes; clamp loop has 3 holes to support oil lines; 2 holes 0.8  0.960 in. Dia., clamp secured together by one screw.  Material:  Stainless steel bandrubber butadiene nitrile cushion  Style Designator:  Hinged & center mtd  |                    |
| Overall Width:  0.830 inches  Center To Center Distance Between Loop And Mounting Hole:  2.330 inches  Loop Inside Diameter:  0.960 inches  Special Features:  Clamp is hinged with two attached brackets, four moubting holes; clamp loop has 3 holes to support oil lines; 2 holes 0.8  0.960 in. Dia., clamp secured together by one screw.  Material:  Stainless steel bandrubber butadiene nitrile cushion  Style Designator:  Hinged & center mtd  |                    |
| Center To Center Distance Between Loop And Mounting Hole: 2.330 inches  Loop Inside Diameter: 0.960 inches  Special Features: Clamp is hinged with two attached brackets, four moubting holes; clamp loop has 3 holes to support oil lines; 2 holes 0.8 0.960 in. Dia., clamp secured together by one screw.  Material: Stainless steel bandrubber butadiene nitrile cushion  Style Designator: Hinged & center mtd  |                    |
| Center To Center Distance Between Loop And Mounting Hole:  2.330 inches  Loop Inside Diameter: 0.960 inches  Special Features: Clamp is hinged with two attached brackets, four moubting holes; clamp loop has 3 holes to support oil lines; 2 holes 0.8 0.960 in. Dia., clamp secured together by one screw.  Material: Stainless steel bandrubber butadiene nitrile cushion  Style Designator: Hinged & center mtd   |                    |
| 2.330 inches  Loop Inside Diameter: 0.960 inches  Special Features: Clamp is hinged with two attached brackets, four moubting holes; clamp loop has 3 holes to support oil lines; 2 holes 0.8 0.960 in. Dia., clamp secured together by one screw.  Material: Stainless steel bandrubber butadiene nitrile cushion  Style Designator: Hinged & center mtd  |                    |
| Loop Inside Diameter:  0.960 inches  Special Features:  Clamp is hinged with two attached brackets, four moubting holes; clamp loop has 3 holes to support oil lines; 2 holes 0.8 0.960 in. Dia., clamp secured together by one screw.  Material:  Stainless steel bandrubber butadiene nitrile cushion  Style Designator:  Hinged & center mtd  |                    |
| 0.960 inches  Special Features:  Clamp is hinged with two attached brackets, four moubting holes; clamp loop has 3 holes to support oil lines; 2 holes 0.8 0.960 in. Dia., clamp secured together by one screw.  Material:  Stainless steel bandrubber butadiene nitrile cushion  Style Designator:  Hinged & center mtd   |                    |
| Special Features:  Clamp is hinged with two attached brackets, four moubting holes; clamp loop has 3 holes to support oil lines; 2 holes 0.8 0.960 in. Dia., clamp secured together by one screw.  Material:  Stainless steel bandrubber butadiene nitrile cushion  Style Designator:  Hinged & center mtd   |                    |
| Clamp is hinged with two attached brackets, four moubting holes; clamp loop has 3 holes to support oil lines; 2 holes 0.8 0.960 in. Dia., clamp secured together by one screw.  Material: Stainless steel bandrubber butadiene nitrile cushion  Style Designator: Hinged & center mtd  |                    |
| 0.960 in. Dia., clamp secured together by one screw.  Material: Stainless steel bandrubber butadiene nitrile cushion  Style Designator: Hinged & center mtd  |                    |
| Material: Stainless steel bandrubber butadiene nitrile cushion Style Designator: Hinged & center mtd   | 10 in. Dia; 1 hole |
| Stainless steel bandrubber butadiene nitrile cushion  Style Designator:  Hinged & center mtd   |                    |
| Style Designator: Hinged & center mtd  |                    |
| Hinged & center mtd  |                    |
|  |                    |
| Shelf Life:  |                    |
|  |                    |
| N/a  |                    |
| Unit Of Measure:   |                    |
|  |                    |
| Demilitarization:  |                    |
| No   |                    |
| Fiig:  |                    |
| A12700   |                    |