

View Online at <https://aerobasegroup.com/nsn/5340-01-376-9482>

First Leg Length:

40.0 millimeters

Second Leg Length:

40.0 millimeters

Second Leg Width:

50.0 millimeters

First Leg Hole Diameter:

Between 8.4 millimeters and 8.8 millimeters

Second Leg Hole Diameter:

Between 12.4 millimeters and 12.8 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

25.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

20.0 millimeters

First Leg Thickness:

4.0 millimeters

Second Leg Thickness:

4.0 millimeters

Center Section Width:

40.0 millimeters

Center Section Thickness:

4.0 millimeters

First Leg Width:

50.0 millimeters

First Leg Distance Between Hole Centers Along Width:

38.1 millimeters

First Leg Distance From Edge To Hole Center Along Width:

6.0 millimeters

First Leg Distance From Edge To Hole Center Along Length:

15.0 millimeters

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

Between 7.0 radians and 9.0 radians

Second Leg Angle:

Between 7.0 radians and 9.0 radians

Material:

Steel uns k02500

Material Specification:

Astm a570 grade 36 assn standard single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.