## NSN 5340-01-377-0095

Access Cover - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-377-0095

Flat Hole Diameter: 0.177 inches Edge Shape: Rectangle, multi holes Length: 6.000 inches Hole Quantity Along Length: 4 Hole Quantity Along Width: 4 Distance Between Holes Along Length: 3.000 inches Distance Between Hole Centerline And First Hole Along Length: 1.250 inches Distance Between Hole Centerline And First Hole Along Width: 1.375 inches Distance From First Hole Centerline To End Along Length: 6.125 inches Body Thickness: 0.063 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer Material: Aluminum alloy Shelf Life:
Control inches Edge Shape: Rectangle, multi holes Length: 6.000 inches Hole Quantity Along Length: 4 Hole Quantity Along Width: 4 Distance Between Holes Along Length: 3.000 inches Distance Between Hole Centerline And First Hole Along Length: 1.250 inches Distance Between Hole Centerline And First Hole Along Width: 1.375 inches Distance From First Hole Centerline To End Along Length: 6.125 inches Body Thickness: 0.063 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer Material: Aluminum alloy
Edge Shape: Rectangle, multi holes Length: 6.000 inches Hole Quantity Along Length: 4 Hole Quantity Along Width: 4 Distance Between Holes Along Length: 3.000 inches Distance Between Hole Centerline And First Hole Along Length: 1.250 inches Distance Between Hole Centerline And First Hole Along Width: 1.375 inches Distance From First Hole Centerline To End Along Length: 6.125 inches Body Thickness: 0.063 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer Material: Aluminum alloy
Rectangle, multi holes  Length: 6.000 inches  Hole Quantity Along Length: 4  Hole Quantity Along Width: 4  Distance Between Holes Along Length: 3.000 inches  Distance Between Hole Centerline And First Hole Along Length: 1.250 inches  Distance Between Hole Centerline And First Hole Along Width: 1.375 inches  Distance From First Hole Centerline To End Along Length: 6.125 inches  Body Thickness: 0.063 inches  Securing Device Type: Threaded fastener  Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer  Material: Aluminum alloy
Length: 6.000 inches Hole Quantity Along Length: 4 Hole Quantity Along Width: 4 Distance Between Holes Along Length: 3.000 inches Distance Between Hole Centerline And First Hole Along Length: 1.250 inches Distance Between Hole Centerline And First Hole Along Width: 1.375 inches Distance From First Hole Centerline To End Along Length: 6.125 inches Body Thickness: 0.063 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer Material: Aluminum alloy
6.000 inches Hole Quantity Along Length: 4 Hole Quantity Along Width: 4 Distance Between Holes Along Length: 3.000 inches Distance Between Hole Centerline And First Hole Along Length: 1.250 inches Distance Between Hole Centerline And First Hole Along Width: 1.375 inches Distance From First Hole Centerline To End Along Length: 6.125 inches Body Thickness: 0.063 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer Material: Aluminum alloy
Hole Quantity Along Length: 4 Hole Quantity Along Width: 4 Distance Between Holes Along Length: 3.000 inches Distance Between Hole Centerline And First Hole Along Length: 1.250 inches Distance Between Hole Centerline And First Hole Along Width: 1.375 inches Distance From First Hole Centerline To End Along Length: 6.125 inches Body Thickness: 0.063 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer Material: Aluminum alloy
Hole Quantity Along Width:  Distance Between Holes Along Length: 3.000 inches  Distance Between Hole Centerline And First Hole Along Length: 1.250 inches  Distance Between Hole Centerline And First Hole Along Width: 1.375 inches  Distance From First Hole Centerline To End Along Length: 6.125 inches  Body Thickness: 0.063 inches  Securing Device Type: Threaded fastener  Mounting Opening Shape Style: Unthreaded hole  End Application: Mk67mod9, console, control officer  Material: Aluminum alloy
Hole Quantity Along Width:  4  Distance Between Holes Along Length: 3.000 inches  Distance Between Hole Centerline And First Hole Along Length: 1.250 inches  Distance Between Hole Centerline And First Hole Along Width: 1.375 inches  Distance From First Hole Centerline To End Along Length: 6.125 inches  Body Thickness: 0.063 inches  Securing Device Type: Threaded fastener  Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer  Material: Aluminum alloy
Distance Between Holes Along Length: 3.000 inches Distance Between Hole Centerline And First Hole Along Length: 1.250 inches Distance Between Hole Centerline And First Hole Along Width: 1.375 inches Distance From First Hole Centerline To End Along Length: 6.125 inches Body Thickness: 0.063 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer Material: Aluminum alloy
Distance Between Holes Along Length: 3.000 inches Distance Between Hole Centerline And First Hole Along Length: 1.250 inches Distance Between Hole Centerline And First Hole Along Width: 1.375 inches Distance From First Hole Centerline To End Along Length: 6.125 inches Body Thickness: 0.063 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer Material: Aluminum alloy
3.000 inches  Distance Between Hole Centerline And First Hole Along Length: 1.250 inches  Distance Between Hole Centerline And First Hole Along Width: 1.375 inches  Distance From First Hole Centerline To End Along Length: 6.125 inches  Body Thickness: 0.063 inches  Securing Device Type: Threaded fastener  Mounting Opening Shape Style: Unthreaded hole  End Application: Mk67mod9, console, control officer  Material: Aluminum alloy
Distance Between Hole Centerline And First Hole Along Length: 1.250 inches Distance Between Hole Centerline And First Hole Along Width: 1.375 inches Distance From First Hole Centerline To End Along Length: 6.125 inches Body Thickness: 0.063 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer Material: Aluminum alloy
1.250 inches  Distance Between Hole Centerline And First Hole Along Width: 1.375 inches  Distance From First Hole Centerline To End Along Length: 6.125 inches  Body Thickness: 0.063 inches  Securing Device Type: Threaded fastener  Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer  Material: Aluminum alloy
Distance Between Hole Centerline And First Hole Along Width:  1.375 inches  Distance From First Hole Centerline To End Along Length:  6.125 inches  Body Thickness:  0.063 inches  Securing Device Type: Threaded fastener  Mounting Opening Shape Style: Unthreaded hole  End Application:  Mk67mod9, console, control officer  Material:  Aluminum alloy
1.375 inches  Distance From First Hole Centerline To End Along Length: 6.125 inches  Body Thickness: 0.063 inches  Securing Device Type: Threaded fastener  Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer  Material: Aluminum alloy
Distance From First Hole Centerline To End Along Length: 6.125 inches Body Thickness: 0.063 inches Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer Material: Aluminum alloy
6.125 inches  Body Thickness: 0.063 inches  Securing Device Type: Threaded fastener  Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer  Material: Aluminum alloy
Body Thickness:  0.063 inches  Securing Device Type: Threaded fastener  Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer  Material: Aluminum alloy
0.063 inches  Securing Device Type: Threaded fastener  Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer  Material: Aluminum alloy
Securing Device Type: Threaded fastener Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer Material: Aluminum alloy
Threaded fastener  Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer Material: Aluminum alloy
Mounting Opening Shape Style: Unthreaded hole End Application: Mk67mod9, console, control officer Material: Aluminum alloy
Unthreaded hole  End Application:  Mk67mod9, console, control officer  Material:  Aluminum alloy
End Application: Mk67mod9, console, control officer Material: Aluminum alloy
Mk67mod9, console, control officer  Material:  Aluminum alloy
Material: Aluminum alloy
Aluminum alloy
•
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A531c0