## NSN 5340-01-377-0730



Angle Bracket - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5340-01-377-0730 **Mounting Hole Type:** Plain First Leg Length: 65.0 millimeters Second Leg Length: 100.0 millimeters Second Leg Width: 210.0 millimeters First Leg Hole Diameter: 17.5 millimeters Second Leg Hole Diameter: 16.0 millimeters Second Leg Distance From Edge To Hole Center Along Width: 25.0 millimeters **Second Leg Distance From Edge To Hole Center Along Length:** 25.0 millimeters First Leg Thickness: 8.0 millimeters Second Leg Thickness: 8.0 millimeters First Leg Width: 210.0 millimeters First Leg End Width: 158.0 millimeters First Leg Distance Between Hole Centers Along Width: 98.0 millimeters First Leg Distance From Edge To Hole Center Along Width: 29.7 millimeters First Leg Distance From Edge To Hole Center Along Length: 32.8 millimeters Second Leg End Radius: 25.0 millimeters First Leg Style: Angle First Leg Hole Arrangement Style: Two holes Second Leg Style:

End radius **Second Leg Hole Arrangement Style:** Second Leg Relationship To First Leg: Not identical

## NSN 5340-01-377-0730

Angle Bracket - Page 2 of 2

Mil-c-46168 spec.



| First Leg Angle:   |
|--|
| 90.0 degrees   |
| Material:  |
| Steel  |
| Material Specification:  |
| Astm a572 grade 50 assn standard single material response  |
| Surface Treatment:   |
| Plastic polyurethane   |
| Surface Treatment Specification:   |
| Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response |
| Style Designator:  |
| Angle  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A042a0   |
| Mil-std (military Standard):   |