

View Online at <https://aerobasegroup.com/nsn/5340-01-377-0893>

Mounting Hole Diameter:

Between 9.4 millimeters and 10.6 millimeters

First Leg Length:

Between 39.0 millimeters and 43.0 millimeters

Second Leg Length:

Between 68.0 millimeters and 72.0 millimeters

Second Leg Width:

32.0 millimeters

First Leg Hole Diameter:

Between 9.4 millimeters and 10.6 millimeters

Second Leg Hole Diameter:

Between 9.4 millimeters and 10.6 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

16.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

37.0 millimeters

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

Center Section Height:

Between 74.0 millimeters and 78.0 millimeters

Center Section Width:

0.125 inches

Center Section Thickness:

32.0 millimeters

First Leg Width:

32.0 millimeters

First Leg Distance Between Hole Centers Along Length:

19.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

16.0 millimeters

First Leg Distance From Edge To Hole Center Along Length:

15.0 millimeters

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

3.0 radians

Second Leg Angle:

3.0 radians

Material:

Steel comp 1009

Material Specification:

Astm a569 assn standard single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.