

View Online at <https://aerobasegroup.com/nsn/5340-01-377-1106>

**Mounting Hole Type:**

Plain

**First Leg Length:**

65.0 millimeters

**Second Leg Length:**

101.0 millimeters

**Second Leg Width:**

210.0 millimeters

**First Leg Hole Diameter:**

17.0 millimeters

**Second Leg Hole Diameter:**

16.0 millimeters

**Second Leg Distance From Edge To Hole Center Along Width:**

25.0 millimeters

**Second Leg Distance From Edge To Hole Center Along Length:**

25.0 millimeters

**First Leg Thickness:**

8.0 millimeters

**Second Leg Thickness:**

8.0 millimeters

**First Leg Width:**

210.0 millimeters

**First Leg End Width:**

158.0 millimeters

**First Leg Distance Between Hole Centers Along Width:**

123.8 millimeters

**First Leg Distance From Edge To Hole Center Along Width:**

56.4 millimeters

**First Leg Distance From Edge To Hole Center Along Length:**

32.8 millimeters

**Second Leg End Radius:**

25.0 millimeters

**First Leg Style:**

Angle

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

End radius

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Opposite p/n 12414324 cagec 19207; 2nd leg I shaped with rt side tapered to 35.0 mm from styl 102 configuration

**Material:**

Steel

**Material Specification:**

Astm a572 gr 50 assn standard single material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.