

View Online at <https://aerobasegroup.com/nsn/5340-01-377-1536>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 70.4 millimeters and 72.0 millimeters

**Second Leg Length:**

Between 113.5 millimeters and 115.1 millimeters

**Second Leg Width:**

Between 157.9 millimeters and 159.5 millimeters

**Second Leg Hole Diameter:**

Between 9.0 millimeters and 10.0 millimeters

**Second Leg Distance Between Upper Hole Centers Along Width:**

120.6 millimeters

**Second Leg Distance Between Hole Centers Along Length:**

25.4 millimeters

**Second Leg Distance Between First And Second Hole Centers Along Width:**

60.3 millimeters

**Second Leg Distance From Edge To Hole Center Along Width:**

10.0 millimeters

**Second Leg Distance From Edge To Hole Center Along Length:**

25.4 millimeters

**First Leg Thickness:**

6.0 millimeters

**Second Leg Thickness:**

6.0 millimeters

**First Leg Width:**

Between 157.9 millimeters and 159.5 millimeters

**First Leg Distance Between Hole Centers Along Width:**

95.7 millimeters

**First Leg Distance Between Hole Centers Along Length:**

21.2 millimeters

**First Leg Distance From Edge To Hole Center Along Width:**

44.0 millimeters

**First Leg Distance From Edge To Hole Center Along Length:**

19.0 millimeters

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Three holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Steel

**Material Specification:**

Astm a715 gr 50 assn standard single material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response and mil-c-53039 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.