

View Online at <https://aerobasegroup.com/nsn/5340-01-377-1536>

Mounting Hole Type:

Plain

First Leg Length:

Between 70.4 millimeters and 72.0 millimeters

Second Leg Length:

Between 113.5 millimeters and 115.1 millimeters

Second Leg Width:

Between 157.9 millimeters and 159.5 millimeters

Second Leg Hole Diameter:

Between 9.0 millimeters and 10.0 millimeters

Second Leg Distance Between Upper Hole Centers Along Width:

120.6 millimeters

Second Leg Distance Between Hole Centers Along Length:

25.4 millimeters

Second Leg Distance Between First And Second Hole Centers Along Width:

60.3 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

10.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

25.4 millimeters

First Leg Thickness:

6.0 millimeters

Second Leg Thickness:

6.0 millimeters

First Leg Width:

Between 157.9 millimeters and 159.5 millimeters

First Leg Distance Between Hole Centers Along Width:

95.7 millimeters

First Leg Distance Between Hole Centers Along Length:

21.2 millimeters

First Leg Distance From Edge To Hole Center Along Width:

44.0 millimeters

First Leg Distance From Edge To Hole Center Along Length:

19.0 millimeters

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel

Material Specification:

Astm a715 gr 50 assn standard single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response and mil-c-53039 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.