## NSN 5340-01-377-1537

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-377-1537

**Mounting Hole Type:** 

Plain

First Leg Length:

Between 81.0 millimeters and 83.0 millimeters

Second Leg Length:

Between 113.0 millimeters and 115.0 millimeters

Second Leg Width:

Between 157.0 millimeters and 159.0 millimeters

Second Leg Hole Diameter:

Between 9.0 millimeters and 10.0 millimeters

Second Leg Distance Between Upper Hole Centers Along Width:

120.6 millimeters

Second Leg Distance Between Hole Centers Along Length:

25.4 major inches

Second Leg Distance Between First And Second Hole Centers Along Width:

60.3 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

25.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

14.6 millimeters

First Leg Thickness:

6.0 millimeters

Second Leg Thickness:

6.0 millimeters

First Leg Width:

Between 157.0 millimeters and 159.0 millimeters

First Leg Hole Arrangement Style:

Three holes

Second Leg Style:

Square

**Second Leg Hole Arrangement Style:** 

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel

**Material Specification:** 

Astm a36 assn standard single material response

**Surface Treatment:** 

Plastic polyurethane

## NSN 5340-01-377-1537

Angle Bracket - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

A:I -	40400	:1:4					!! -	E0000 ::::	arv specificatio	:	4	
\/III_C	' <u>-</u> 4h1hX	military	SUBCITICATION	SIDUIE TE	atment r	BSNANSE A	r mii-c	-5 KU KU MIIITS	arv sneciticatio	n sinale	treatment	resnonse

Style Designator:

Angle

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.