

View Online at <https://aerobasegroup.com/nsn/5340-01-377-2457>

Mounting Hole Type:

Plain

First Leg Length:

Between 50.0 millimeters and 52.0 millimeters

Second Leg Length:

Between 160.3 millimeters and 162.3 millimeters

Second Leg Width:

Between 46.0 millimeters and 48.0 millimeters

First Leg Hole Diameter:

Between 17.40 millimeters and 17.75 millimeters

Second Leg Hole Diameter:

Between 9.92 millimeters and 10.20 millimeters

Second Leg Distance Between Hole Centers Along Length:

49.8 major mils and 51.8 major centimeters

Second Leg Distance From Edge To Hole Center Along Width:

Between 15.5 millimeters and 17.5 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

Between 18.1 millimeters and 20.1 millimeters

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

Between 46.0 millimeters and 48.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

Between 21.4 millimeters and 23.4 millimeters

First Leg Distance From Edge To Hole Center Along Length:

Between 19.8 millimeters and 21.8 millimeters

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel

Material Specification:

Astm a28 assn standard single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.