

View Online at <https://aerobasegroup.com/nsn/5340-01-377-2468>

Mounting Hole Type:

Plain

First Leg Length:

Between 57.0 millimeters and 59.0 millimeters

Second Leg Length:

Between 131.0 millimeters and 133.0 millimeters

Second Leg Width:

Between 47.0 millimeters and 49.0 millimeters

First Leg Hole Diameter:

Between 9.92 millimeters and 10.20 millimeters

Second Leg Hole Diameter:

Between 10.92 millimeters and 11.20 millimeters

Second Leg Distance Between Hole Centers Along Width:

25.0 millimeters

Second Leg Distance Between Hole Centers Along Length:

45.0 major inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 10.0 millimeters and 12.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

Between 37.0 millimeters and 39.0 millimeters

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

Between 47.0 millimeters and 49.0 millimeters

First Leg Distance Between Hole Centers Along Width:

24.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

Between 11.0 millimeters and 13.0 millimeters

First Leg Distance From Edge To Hole Center Along Length:

Between 20.0 millimeters and 22.0 millimeters

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Steel

Material Specification:

Astm a28 assn standard single material response

Surface Treatment:

Plastic polyurethane

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.