NSN 5340-01-377-2468

Angle Bracket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-377-2468

Mounting Hole Type:

Plain

First Leg Length:

Between 57.0 millimeters and 59.0 millimeters

Second Leg Length:

Between 131.0 millimeters and 133.0 millimeters

Second Leg Width:

Between 47.0 millimeters and 49.0 millimeters

First Leg Hole Diameter:

Between 9.92 millimeters and 10.20 millimeters

Second Leg Hole Diameter:

Between 10.92 millimeters and 11.20 millimeters

Second Leg Distance Between Hole Centers Along Width:

25.0 millimeters

Second Leg Distance Between Hole Centers Along Length:

45.0 major inches

Second Leg Distance From Edge To Hole Center Along Width:

Between 10.0 millimeters and 12.0 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

Between 37.0 millimeters and 39.0 millimeters

First Leg Thickness:

0.250 inches

Second Leg Thickness:

0.250 inches

First Leg Width:

Between 47.0 millimeters and 49.0 millimeters

First Leg Distance Between Hole Centers Along Width:

24.0 millimeters

First Leg Distance From Edge To Hole Center Along Width:

Between 11.0 millimeters and 13.0 millimeters

First Leg Distance From Edge To Hole Center Along Length:

Between 20.0 millimeters and 22.0 millimeters

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

NSN 5340-01-377-2468

Angle Bracket - Page 2 of 2



First Leg Angle:
90.0 degrees
Material:
Steel
Material Specification:
Astm a28 assn standard single material response
Surface Treatment:
Plastic polyurethane
Surface Treatment Specification:
Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response
Style Designator:
Angle
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A042a0
Mil-std (military Standard):
Mil-c-46168 spec.