NSN 5340-01-377-3335

Spacing Threaded Standoff - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5340-01-377-3338 |
|---|
| Thread Class: |
| 2b left internal (includes through thread) |
| Thread Direction: |
| Right-hand left internal (includes through thread) |
| Thread Length: |
| 0.362 inches left internal (includes through thread) |
| Diameter: |
| 0.250 inches |
| Length: |
| Between 0.698 inches and 0.702 inches |
| Cross-sectional Shape: |
| Round |
| Thready Qty Per Inch (tpi): |
| 32 left internal (includes through thread) |
| Thread Size: |
| 0.138 inches left internal (includes through thread) |
| Left Projection Diameter: |
| Between 0.175 inches and 0.180 inches |
| Left Projection Length: |
| Between 0.100 inches and 0.110 inches |
| Material: |
| Aluminum alloy 2017 |
| Material Specification: |
| Qq-a-225/5 t4 federal specification single material response |
| Surface Treatment: |
| Chromate |
| Surface Treatment Specification: |
| Mil-c-5541 cl 1a military specification single treatment response |
| Style Designator: |
| Projection one end left internal thread |
| Thread Series Designator: |
| Unc left internal (includes through thread) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fila: |

A08900

Mil-std (military Standard):

Mil-c-5541 spec.