

View Online at <https://aerobasegroup.com/nsn/5340-01-378-4024>

**First Leg Length:**

0.750 inches

**Second Leg Length:**

4.060 inches

**Second Leg Width:**

4.380 inches

**Second Leg Corner Radius:**

0.190 inches

**First Leg Hole Diameter:**

Between 0.250 inches and 0.255 inches

**Second Leg Hole Diameter:**

0.188 inches

**Second Leg Distance Between Hole Centers Along Width:**

3.750 inches

**Second Leg Distance Between Hole Centers Along Length:**

2.750 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.310 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.280 inches

**First Leg Thickness:**

0.090 inches

**Second Leg Thickness:**

0.090 inches

**First Leg Width:**

4.380 inches

**First Leg Distance Between Hole Centers Along Width:**

1.750 inches

**First Leg Distance From Edge To Hole Center Along Width:**

1.940 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.280 inches and 0.290 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

Four holes

**Features Provided:**

Nut

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

0.090 radians

**Special Features:**

Support includes six captive nuts; p/n cls632-3 and p/n class032-2

**Material:**

Aluminum alloy 5052

**Material Specification:**

Qq-a-250/8 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, class 1 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.