

View Online at <https://aerobasegroup.com/nsn/5340-01-378-4024>

First Leg Length:

0.750 inches

Second Leg Length:

4.060 inches

Second Leg Width:

4.380 inches

Second Leg Corner Radius:

0.190 inches

First Leg Hole Diameter:

Between 0.250 inches and 0.255 inches

Second Leg Hole Diameter:

0.188 inches

Second Leg Distance Between Hole Centers Along Width:

3.750 inches

Second Leg Distance Between Hole Centers Along Length:

2.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.310 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.280 inches

First Leg Thickness:

0.090 inches

Second Leg Thickness:

0.090 inches

First Leg Width:

4.380 inches

First Leg Distance Between Hole Centers Along Width:

1.750 inches

First Leg Distance From Edge To Hole Center Along Width:

1.940 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.280 inches and 0.290 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

Four holes

Features Provided:

Nut

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

0.090 radians

Special Features:

Support includes six captive nuts; p/n cls632-3 and p/n class032-2

Material:

Aluminum alloy 5052

Material Specification:

Qq-a-250/8 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, class 1 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.