

View Online at <https://aerobasegroup.com/nsn/5340-01-380-0013>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.662 inches

**Second Leg Length:**

1.164 inches

**Second Leg Width:**

2.125 inches

**First Leg Hole Diameter:**

Between 0.144 inches and 0.146 inches

**Second Leg Hole Diameter:**

Between 0.166 inches and 0.169 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.312 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.289 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.189 inches

**First Leg Thickness:**

0.050 inches

**Second Leg Thickness:**

0.050 inches

**First Leg Width:**

2.125 inches

**First Leg Distance Between Hole Centers Along Width:**

0.364 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.975 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.152 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

2 holes 1st leg 0.124 in. Min and 0.129 in. Maximum dia; 1st leg hole 0.187 in. Min and 0.193 in maximum dia; 2nd leg 1 spring clip atch to left side m24066/2-313

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-250/11 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541 cl 3 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.