Spacing Threaded Standoff - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5340-01-380-1577

Thread Class:

2a left internal (includes through thread)

Thread Direction:

Right-hand left internal (includes through thread)

Thread Length:

0.2600 inches left internal (includes through thread)

Length:

0.2400 inches

Cross-sectional Shape:

Hexagon

Width Across Flats:

0.2500 inches

Thready Qty Per Inch (tpi):

32 left internal (includes through thread)

Thread Size:

0.1380 inches left internal (includes through thread)

Right Projection Diameter:

0.1380 inches

Right Projection Length:

0.2600 inches

Material:

Steel comp 303 or steel comp 303 plus x or steel comp 303cu or steel comp 303ma or steel comp 303se or steel comp 416 or steel

comp 416se or steel comp 430f or steel comp 430fse

Material Specification:

Mil-w-52263 military specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-f-14072-e300 military specification single treatment response

Style Designator:

Projection one end w/ right external thread

Thread Series Designator:

Unc left internal (includes through thread)

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A08900

Mil-std (military Standard):

Mil-w-52263 spec.