

View Online at <https://aerobasegroup.com/nsn/5340-01-380-4532>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.800 inches

**Second Leg Length:**

4.300 inches

**Reinforcement Method (non-core):**

Fillet center section

**Second Leg Width:**

0.125 inches

**Second Leg Corner Radius:**

0.250 inches

**Second Leg End Width:**

5.000 inches

**First Leg Hole Diameter:**

Between 0.218 inches and 0.229 inches

**Second Leg Hole Diameter:**

Between 0.218 inches and 0.229 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.400 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.350 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

0.140 inches

**First Leg Corner Radius:**

0.250 inches

**First Leg Distance Between Hole Centers Along Width:**

0.700 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.350 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.400 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Radius foot

**Second Leg Hole Arrangement Style:**

One hole

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Jsecond leg also has a slot mounting at the opposite end of the leg, 0.200 in. Lg by 0.218-0.229 in. Wide; this bracket assembly that is used on a land position target-main landing gear consist pieces -005 and -003

**Material:**

Aluminum alloy 7075 and steel comp 4130

**Material Specification:**

Mil-s-18729 military specification 1st material response and qq-a-250/12 federal specification 2nd material response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-s-18729 spec.