

View Online at <https://aerobasegroup.com/nsn/5340-01-380-4532>

Mounting Hole Type:

Plain

First Leg Length:

0.800 inches

Second Leg Length:

4.300 inches

Reinforcement Method (non-core):

Fillet center section

Second Leg Width:

0.125 inches

Second Leg Corner Radius:

0.250 inches

Second Leg End Width:

5.000 inches

First Leg Hole Diameter:

Between 0.218 inches and 0.229 inches

Second Leg Hole Diameter:

Between 0.218 inches and 0.229 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.400 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.350 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

0.140 inches

First Leg Corner Radius:

0.250 inches

First Leg Distance Between Hole Centers Along Width:

0.700 inches

First Leg Distance From Edge To Hole Center Along Width:

0.350 inches

First Leg Distance From Edge To Hole Center Along Length:

0.400 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Radius foot

Second Leg Hole Arrangement Style:

One hole

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

Jsecond leg also has a slot mounting at the opposite end of the leg, 0.200 in. Lg by 0.218-0.229 in. Wide; this bracket assembly that is used on a land position target-main landing gear consist pieces -005 and -003

Material:

Aluminum alloy 7075 and steel comp 4130

Material Specification:

Mil-s-18729 military specification 1st material response and qq-a-250/12 federal specification 2nd material response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-s-18729 spec.