

View Online at <https://aerobasegroup.com/nsn/5340-01-380-4997>

Mounting Hole Type:

Plain

First Leg Length:

0.687 inches

Second Leg Length:

0.250 inches

End Application:

Pacer dawn

Second Leg Width:

0.375 inches

First Leg Hole Diameter:

0.171 inches

Second Leg Hole Diameter:

0.062 inches

Second Leg Distance Between Hole Centers Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.062 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.156 inches

First Leg Thickness:

0.031 inches

Second Leg Thickness:

0.031 inches

Center Section Height:

1.562 inches

Center Section Width:

0.375 inches

Center Section Thickness:

0.031 inches

First Leg Width:

0.375 inches

First Leg Distance From Edge To Hole Center Along Width:

0.187 inches

First Leg Distance From Edge To Hole Center Along Length:

0.499 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Material:

Aluminum alloy 2024

Material Specification:

Qq-a-250/4 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8625, type 2 gold military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8625 spec.