

View Online at <https://aerobasegroup.com/nsn/5340-01-381-2877>

Cross Sectional Shape:

Flat

Hole Diameter:

Between 0.120 inches and 0.125 inches

Width:

1.020 inches

Edge Shape:

Rectangle, multi holes

Length:

1.426 inches

Corner Radius:

0.060 inches

Hole Quantity Along Width:

4

Distance Between Holes Along Length:

Between 1.140 inches and 1.150 inches

Distance Between Holes Along Width:

Between 0.735 inches and 0.745 inches

Distance From First Hole Centerline To End Along Length:

0.140 inches

Distance From First Hole Centerline To End Along Width:

0.140 inches

Body Thickness:

0.080 inches

Securing Device Type:

Special

Mounting Opening Shape Style:

Unthreaded hole

End Application:

Pacer dawn

Special Features:

Paint color no. 17875 per fed-std-595; mtg holes csk 82 degrees to 0.250 diameter max

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Anodize or primer or paint polyurethane

Surface Treatment Specification:

Mil-a-8625, type 2, cl 1 military specification 1st treatment response or mil-p-23377 military specification 2nd treatment response or mil-c-83286 military specification 3rd treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A531c0

Mil-std (military Standard):

Mil-a-8625 spec.