

View Online at <https://aerobasegroup.com/nsn/5340-01-381-3871>

Mounting Hole Type:

Plain

First Leg Length:

Between 24.4 millimeters and 26.4 millimeters

Second Leg Length:

Between 85.0 millimeters and 89.0 millimeters

Second Leg Width:

Between 223.6 millimeters and 227.6 millimeters

First Leg Hole Diameter:

Between 6.7 millimeters and 7.3 millimeters

Second Leg Hole Diameter:

Between 9.0 millimeters and 11.0 millimeters

Second Leg Distance Between Hole Centers Along Width:

Between 95.9 millimeters and 99.9 millimeters

Second Leg Distance From Edge To Hole Center Along Width:

116.6 millimeters

Second Leg Distance From Edge To Hole Center Along Length:

8.0 millimeters

First Leg Thickness:

0.125 inches

Second Leg Thickness:

0.125 inches

First Leg Width:

Between 223.6 millimeters and 227.6 millimeters

First Leg Distance Between Hole Centers Along Width:

203.4 millimeters

First Leg Distance From Edge To Hole Center Along Width:

11.1 millimeters

First Leg Distance From Edge To Hole Center Along Length:

11.1 millimeters

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

One hole near edge on second leg has 5.7 mm min 6.3 mm maximum dia

Material:

Aluminum alloy 6061

Surface Treatment:

Paint

Surface Treatment Specification:

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-46168 spec.