

View Online at <https://aerobasegroup.com/nsn/5340-01-381-3871>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 24.4 millimeters and 26.4 millimeters

**Second Leg Length:**

Between 85.0 millimeters and 89.0 millimeters

**Second Leg Width:**

Between 223.6 millimeters and 227.6 millimeters

**First Leg Hole Diameter:**

Between 6.7 millimeters and 7.3 millimeters

**Second Leg Hole Diameter:**

Between 9.0 millimeters and 11.0 millimeters

**Second Leg Distance Between Hole Centers Along Width:**

Between 95.9 millimeters and 99.9 millimeters

**Second Leg Distance From Edge To Hole Center Along Width:**

116.6 millimeters

**Second Leg Distance From Edge To Hole Center Along Length:**

8.0 millimeters

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

Between 223.6 millimeters and 227.6 millimeters

**First Leg Distance Between Hole Centers Along Width:**

203.4 millimeters

**First Leg Distance From Edge To Hole Center Along Width:**

11.1 millimeters

**First Leg Distance From Edge To Hole Center Along Length:**

11.1 millimeters

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

One hole near edge on second leg has 5.7 mm min 6.3 mm maximum dia

**Material:**

Aluminum alloy 6061

**Surface Treatment:**

Paint

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.