# NSN 5340-01-381-3880

Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-381-3880

# Thread Class:

2b left internal (includes through thread)

# Thread Direction:

Right-hand left internal (includes through thread)

# Thread Length:

0.700 inches left internal (includes through thread)

# Diameter:

Between 0.216 inches and 0.222 inches

## Length:

Between 0.433 inches and 0.443 inches

# **Cross-sectional Shape:**

Round

Thready Qty Per Inch (tpi):

40 left internal (includes through thread)

#### Thread Size:

0.112 inches left internal (includes through thread)

#### **Right Projection Diameter:**

Between 0.177 inches and 0.181 inches

#### **Right Projection Length:**

Between 0.070 inches and 0.080 inches

## Special Features:

Knurled surface

## Material:

Stainless steel

## **Material Specification:**

Astm a555 assn standard single material response or astm a581 assn standard single material response

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Mil-f-14072 e300 military specification single treatment response

#### Style Designator:

Projection one end

## **Thread Series Designator:**

Unc left internal (includes through thread)

#### Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A08900

Spacing Threaded Standoff - Page 2 of 2

Mil-std (military Standard):

Mil-f-14072 spec.

