

View Online at <https://aerobasegroup.com/nsn/5340-01-381-3941>

**Mounting Hole Type:**

Plain

**First Leg Length:**

18.0 millimeters

**Second Leg Length:**

Between 74.7 millimeters and 77.7 millimeters

**Second Leg Width:**

12.7 millimeters

**First Leg Hole Diameter:**

9.4 millimeters

**Second Leg Hole Diameter:**

Between 7.1 millimeters and 7.2 millimeters

**Second Leg Distance Between Hole Centers Along Length:**

7.1 major inches

**Second Leg Distance From Edge To Hole Center Along Width:**

6.4 millimeters

**Second Leg Distance From Edge To Hole Center Along Length:**

8.5 millimeters

**First Leg Thickness:**

0.125 inches

**Second Leg Thickness:**

0.125 inches

**First Leg Width:**

12.8 millimeters

**First Leg Distance From Edge To Hole Center Along Width:**

6.4 millimeters

**First Leg Distance From Edge To Hole Center Along Length:**

6.4 millimeters

**First Leg End Radius:**

6.4 millimeters

**First Leg Style:**

End radius

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Finish color green

**Material:**

Aluminum alloy 6063

**Material Specification:**

Qq-a-200/9 federal specification single material response or astmb221 assn standard single material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response or mil-c-53039 assn standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.