

View Online at <https://aerobasegroup.com/nsn/5340-01-381-9747>

**Mounting Hole Type:**

Plain

**First Leg Length:**

71.1 millimeters

**Second Leg Length:**

75.0 millimeters

**End Application:**

Mrap - common nsn - used on mrap no permanent wsd identified and 1 other weapon system

**Second Leg Width:**

1176.0 millimeters

**Second Leg End Width:**

146.0 millimeters

**First Leg Hole Diameter:**

8.7 millimeters

**Second Leg Distance Between Hole Centers Along Width:**

146.0 millimeters

**Second Leg Distance From Edge To Hole Center Along Width:**

20.3 millimeters

**Second Leg Slot Length:**

11.8 millimeters

**Second Leg Slot Width:**

8.7 millimeters

**First Leg Thickness:**

0.119 inches

**Second Leg Thickness:**

0.119 inches

**First Leg Width:**

76.2 millimeters

**First Leg Distance Between Hole Centers Along Width:**

38.1 millimeters

**First Leg Distance From Edge To Hole Center Along Width:**

18.2 major inches

**First Leg Distance From Edge To Hole Center Along Length:**

18.2 major inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square and tapered

**Second Leg Hole Arrangement Style:**

4 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

Top slots on 2nd leg 37.8 mm apart along lg

**Material:**

Steel

**Material Specification:**

Astma36 assn standard single material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response or mil-c-53039 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.