

View Online at <https://aerobasegroup.com/nsn/5340-01-382-7495>

Mounting Hole Type:

Plain

First Leg Length:

2.250 inches

Second Leg Length:

3.250 inches

Reinforcement Method (non-core):

Turned edge both legs

Second Leg Width:

3.120 inches

First Leg Hole Diameter:

Between 0.195 inches and 0.255 inches

Second Leg Hole Diameter:

1.500 inches

Second Leg Distance Between Upper Hole Centers Along Width:

2.250 inches

Second Leg Distance Between Hole Centers Along Length:

1.375 inches

Second Leg Distance Between First And Second Hole Centers Along Width:

1.125 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.136 inches

Second Leg Distance From Edge To Hole Center Along Length:

Between 0.310 inches and 0.440 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

Center Section Height:

Between 0.970 inches and 1.030 inches

Center Section Width:

3.120 inches

Center Section Thickness:

0.063 inches

First Leg Width:

1.500 inches

First Leg End Width:

1.000 inches

First Leg Distance From Edge To Hole Center Along Width:

0.750 inches

First Leg Distance From Edge To Hole Center Along Length:

1.000 inches

First Leg Style:

Chamfered ends

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

First Leg Chamfer Angle:

45.0 degrees

Special Features:

Hole through both legs 0.515 in. Min and 0.540 in. Maximum dia

Material:

Aluminum alloy 5086 or aluminum alloy 5083

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541 military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.