## NSN 5340-01-383-4016

Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-383-4016 **Thread Class:** 2b right internal **Thread Direction:** Left-hand right internal Thread Length: 0.500 inches right internal **Hole Diameter:** Between 0.148 inches and 0.153 inches Length: Between 0.495 inches and 0.505 inches **Cross-sectional Shape:** Hexagon Width Across Flats: Between 0.245 inches and 0.255 inches Thready Qty Per Inch (tpi): 40 right internal **Thread Size:** 0.112 inches right internal **Right Projection Diameter:** Between 0.185 inches and 0.188 inches **Right Projection Length:** Between 0.072 inches and 0.078 inches Material: Aluminum alloy 6061 standoff **Material Specification:** Qq-a-225/6, t4 federal specification single material response standoff **Surface Treatment:** Anodize standoff **Surface Treatment Specification:** Mil-a-8625, type f military specification single treatment response standoff or mil-a-8625 type 2, cl 1 military specification 1st treatment response standoff **Style Designator:** Projection one end left internal thread **Thread Series Designator:** Unc right internal **Specification Data:** 80205-nas1830 professional/industrial association standard Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5340-01-383-4016

Spacing Threaded Standoff - Page 2 of 2



Fiig:

A08900

Mil-std (military Standard):

Mil-a-8625 spec.