NSN 5340-01-384-7394

Double Angle Bracket - Page 1 of 2

Mounting Hole Type:



View Online at https://aerobasegroup.com/nsn/5340-01-384-7394

| Plain |
|--|
| First Leg Length: |
| 0.620 inches |
| Second Leg Length: |
| 0.780 inches |
| Second Leg Width: |
| 1.000 inches |
| Second Leg Corner Radius: |
| 0.310 inches |
| Second Leg Hole Diameter: |
| Between 0.197 inches and 0.202 inches |
| Second Leg Distance From Edge To Hole Center Along Width: |
| 0.500 inches |
| Second Leg Distance From Edge To Hole Center Along Length: |
| 0.310 inches |
| First Leg Thickness: |
| Between 0.058 inches and 0.068 inches |
| Second Leg Thickness: |
| Between 0.058 inches and 0.068 inches |
| Center Section Height: |
| 0.500 inches |
| Center Section Width: |
| 1.000 inches |
| Center Section Thickness: |
| Between 0.058 inches and 0.068 inches |
| First Leg Width: |
| 1.000 inches |
| First Leg Corner Radius: |
| 0.120 inches |
| First Leg Style: |
| Corner radius |
| First Leg Hole Arrangement Style: |
| No hole |
| Second Leg Style: |
| Corner radius |
| Second Leg Hole Arrangement Style: |
| One hole |
| Features Provided: |
| Nut |
| Second Leg Relationship To First Leg: |
| Not identical |

NSN 5340-01-384-7394

Double Angle Bracket - Page 2 of 2



| First Leg Angle: |
|---|
| 90.0 degrees |
| Second Leg Angle: |
| 90.0 degrees |
| Material: |
| Aluminum alloy 2024 |
| Material Specification: |
| Qq-a-250/5 temp 0 federal specification single material response |
| Surface Treatment: |
| Anodize |
| Surface Treatment Specification: |
| Mil-a-8625 type 2 cl 1 military specification single treatment response |
| Style Designator: |
| Double angle |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A042a0 |
| Mil-std (military Standard): |
| Mil-a-8625 spec. |
| |