

View Online at <https://aerobasegroup.com/nsn/5340-01-385-1552>

Mounting Hole Type:

Plain

First Leg Length:

3.430 inches

Second Leg Length:

3.430 inches

Reinforcement Method (non-core):

Gusset both legs

First Leg Hole Diameter:

0.687 inches

First Leg Thickness:

0.080 inches

Second Leg Thickness:

0.080 inches

Center Section Height:

0.080 inches

Center Section Width:

1.690 inches

Center Section Thickness:

0.080 inches

First Leg Width:

1.690 inches

First Leg Distance From Edge To Hole Center Along Width:

0.550 inches

First Leg Distance From Edge To Hole Center Along Length:

0.700 inches

First Leg Distance Between First And Second Hole Centers Along Length:

1.050 inches

First Leg Distance Between Second And Third Hole Centers Along Length:

1.060 inches

First Leg End Radius:

0.600 inches

First Leg Style:

End radius and tapered

First Leg Hole Arrangement Style:

Three holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

90.0 degrees

Second Leg Angle:

90.0 degrees

Special Features:

2 nut plates ms 21075108n riveted to ea leg

Material:

Aluminum alloy 6061

Material Specification:

Qq-a-250/11 federal specification single material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-a-8626 military specification single treatment response

Style Designator:

Adjacent angles

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-a-8626 spec.