

View Online at <https://aerobasegroup.com/nsn/5340-01-385-1752>

Mounting Hole Type:

Plain

First Leg Length:

0.550 inches

Second Leg Length:

0.600 inches

End Application:

Pacer dawn

Second Leg Width:

2.900 inches

Second Leg Corner Radius:

0.120 inches

First Leg Slot Length:

0.220 inches

First Leg Slot Width:

0.140 inches

Second Leg Distance Between Hole Centers Along Width:

2.400 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.200 inches

Second Leg Slot Length:

0.220 inches

Second Leg Slot Width:

0.140 inches

First Leg Thickness:

0.063 inches

Second Leg Thickness:

0.063 inches

First Leg Width:

2.900 inches

First Leg Corner Radius:

0.120 inches

First Leg Distance Between Hole Centers Along Width:

1.608 inches

First Leg Distance From Edge To Hole Center Along Width:

0.610 inches

First Leg Distance From Edge To Hole Center Along Length:

0.200 inches

First Leg Style:

Corner radius

First Leg Hole Arrangement Style:

2 slots

Second Leg Style:

Corner radius

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Material:

Aluminum alloy

Material Specification:

Qq-a-250/8, temp h32 federal specification single material response

Surface Treatment:

Chromate

Surface Treatment Specification:

Mil-c-5541, cl 1a military specification single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0

Mil-std (military Standard):

Mil-c-5541 spec.