

View Online at <https://aerobasegroup.com/nsn/5340-01-385-1752>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.550 inches

**Second Leg Length:**

0.600 inches

**End Application:**

Pacer dawn

**Second Leg Width:**

2.900 inches

**Second Leg Corner Radius:**

0.120 inches

**First Leg Slot Length:**

0.220 inches

**First Leg Slot Width:**

0.140 inches

**Second Leg Distance Between Hole Centers Along Width:**

2.400 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.200 inches

**Second Leg Slot Length:**

0.220 inches

**Second Leg Slot Width:**

0.140 inches

**First Leg Thickness:**

0.063 inches

**Second Leg Thickness:**

0.063 inches

**First Leg Width:**

2.900 inches

**First Leg Corner Radius:**

0.120 inches

**First Leg Distance Between Hole Centers Along Width:**

1.608 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.610 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.200 inches

**First Leg Style:**

Corner radius

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Corner radius

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Material:**

Aluminum alloy

**Material Specification:**

Qq-a-250/8, temp h32 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 1a military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.