

View Online at <https://aerobasegroup.com/nsn/5340-01-385-6772>

**Mounting Hole Type:**

Plain

**First Leg Length:**

0.570 inches

**Second Leg Width:**

0.680 inches

**First Leg Hole Diameter:**

0.112 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.190 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.130 inches

**Second Leg Slot Length:**

0.280 inches

**Second Leg Slot Width:**

Between 0.090 inches and 0.100 inches

**First Leg Thickness:**

0.150 inches

**Second Leg Thickness:**

0.110 inches

**First Leg Width:**

0.300 inches

**First Leg Distance Between Hole Centers Along Length:**

0.275 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.150 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.150 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Angle

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Special Features:**

1st leg mtg holes thd 0.112-40 unc-2b; 2nd leg slots on angle of 38 deg

**Material:**

Aluminum alloy 356.0 or aluminum alloy 2024 or aluminum alloy 6061

**Material Specification:**

Mil-c-1186t6 military specification 1st material response or mil-a-21180 military specification 1st material response or astmb209 t6ort651 assn standard 2nd material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-std-171 military standard single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-1186t6 spec.