

View Online at <https://aerobasegroup.com/nsn/5340-01-385-6772>

Mounting Hole Type:

Plain

First Leg Length:

0.570 inches

Second Leg Width:

0.680 inches

First Leg Hole Diameter:

0.112 inches

Second Leg Distance Between Hole Centers Along Width:

0.190 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.130 inches

Second Leg Slot Length:

0.280 inches

Second Leg Slot Width:

Between 0.090 inches and 0.100 inches

First Leg Thickness:

0.150 inches

Second Leg Thickness:

0.110 inches

First Leg Width:

0.300 inches

First Leg Distance Between Hole Centers Along Length:

0.275 inches

First Leg Distance From Edge To Hole Center Along Width:

0.150 inches

First Leg Distance From Edge To Hole Center Along Length:

0.150 inches

First Leg Style:

Square

First Leg Hole Arrangement Style:

Two holes

Second Leg Style:

Angle

Second Leg Hole Arrangement Style:

2 slots

Second Leg Relationship To First Leg:

Not identical

First Leg Angle:

90.0 degrees

Special Features:

1st leg mtg holes thd 0.112-40 unc-2b; 2nd leg slots on angle of 38 deg

Material:

Aluminum alloy 356.0 or aluminum alloy 2024 or aluminum alloy 6061

Material Specification:

Mil-c-1186t6 military specification 1st material response or mil-a-21180 military specification 1st material response or astmb209 t6ort651
assn standard 2nd material response

Surface Treatment:

Anodize

Surface Treatment Specification:

Mil-std-171 military standard single treatment response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A042a0

Mil-std (military Standard):

Mil-c-1186t6 spec.