# NSN 5340-01-386-7839

Spacing Threaded Standoff - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5340-01-386-7839

#### Thread Class:

2b left internal (includes through thread)

#### Thread Direction:

Right-hand left internal (includes through thread)

#### Thread Length:

0.438 inches left internal (includes through thread)

#### Hole Diameter:

Between 0.148 inches and 0.152 inches

#### Length:

Between 0.433 inches and 0.443 inches

## **Cross-sectional Shape:**

Hexagon

## Width Across Flats:

Between 0.244 inches and 0.256 inches

## Thready Qty Per Inch (tpi):

40 left internal (includes through thread)

#### Thread Size:

0.112 inches left internal (includes through thread)

## **Right Projection Diameter:**

Between 0.185 inches and 0.188 inches

## Right Projection Length:

Between 0.102 inches and 0.108 inches

## Material:

Steel comp 303se or steel comp 203ez

## Material Specification:

Astm a582 assn standard all material responses

#### Surface Treatment:

Passivate

## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

## Style Designator:

Projection one end left internal thread

## Thread Series Designator:

Unc left internal (includes through thread)

## Specification Data:

80205-nas1830 professional/industrial association standard

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5340-01-386-7839

Spacing Threaded Standoff - Page 2 of 2

**Fiig:** A08900

