

View Online at <https://aerobasegroup.com/nsn/5340-01-386-9663>

**Mounting Hole Type:**

Plain

**First Leg Length:**

106.0 millimeters

**Second Leg Length:**

106.0 millimeters

**Second Leg Width:**

110.0 millimeters

**First Leg Hole Diameter:**

17.5 millimeters

**Second Leg Hole Diameter:**

17.5 millimeters

**Second Leg Distance Between Hole Centers Along Width:**

71.0 millimeters

**Second Leg Distance From Edge To Hole Center Along Width:**

20.0 millimeters

**Second Leg Distance From Edge To Hole Center Along Length:**

36.5 millimeters

**First Leg Thickness:**

10.0 millimeters

**Second Leg Thickness:**

10.0 millimeters

**Center Section Height:**

231.0 millimeters

**Center Section Width:**

140.0 millimeters

**Center Section Thickness:**

10.0 millimeters

**First Leg Width:**

140.0 millimeters

**First Leg Distance Between Hole Centers Along Width:**

78.0 millimeters

**First Leg Distance From Edge To Hole Center Along Width:**

20.0 millimeters

**First Leg Distance From Edge To Hole Center Along Length:**

36.5 millimeters

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

Two holes

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

90.0 degrees

**Second Leg Angle:**

90.0 degrees

**Material:**

Steel

**Material Specification:**

Astm a36 assn standard single material response or stm a570 grade 36 assn standard single material response

**Surface Treatment:**

Plastic polyurethane

**Surface Treatment Specification:**

Mil-c-46168 military specification single treatment response

**Style Designator:**

Adjacent angles

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-46168 spec.