

View Online at <https://aerobasegroup.com/nsn/5340-01-387-3706>

Mounting Hole Type:

Plain

First Leg Length:

Between 1.840 inches and 1.900 inches

Second Leg Length:

Between 0.570 inches and 0.630 inches

End Application:

Pacer dawn

Second Leg Width:

Between 1.230 inches and 1.280 inches

First Leg Hole Diameter:

Between 0.230 inches and 0.240 inches

Second Leg Hole Diameter:

Between 0.230 inches and 0.240 inches

Second Leg Distance Between Hole Centers Along Width:

0.750 inches

Second Leg Distance From Edge To Hole Center Along Width:

0.250 inches

Second Leg Distance From Edge To Hole Center Along Length:

0.250 inches

First Leg Thickness:

0.060 inches

Second Leg Thickness:

0.060 inches

First Leg Width:

Between 1.230 inches and 1.280 inches

First Leg End Width:

Between 0.860 inches and 0.920 inches

First Leg Distance From Edge To Hole Center Along Width:

Between 0.430 inches and 0.460 inches

First Leg Distance From Edge To Hole Center Along Length:

Between 0.220 inches and 0.280 inches

First Leg Style:

Square and tapered

First Leg Hole Arrangement Style:

One hole

Second Leg Style:

Square

Second Leg Hole Arrangement Style:

Two holes

Second Leg Relationship To First Leg:

Identical

First Leg Angle:

Between 0.17 radians and 0.23 radians

Special Features:

Drawing title clip, actuator - variable nozzle

Material:

Titanium alloy uns r56400

Material Specification:

Ams4911/ti6al-4v assn standard all material responses

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A042a0