

View Online at <https://aerobasegroup.com/nsn/5340-01-387-3706>

**Mounting Hole Type:**

Plain

**First Leg Length:**

Between 1.840 inches and 1.900 inches

**Second Leg Length:**

Between 0.570 inches and 0.630 inches

**End Application:**

Pacer dawn

**Second Leg Width:**

Between 1.230 inches and 1.280 inches

**First Leg Hole Diameter:**

Between 0.230 inches and 0.240 inches

**Second Leg Hole Diameter:**

Between 0.230 inches and 0.240 inches

**Second Leg Distance Between Hole Centers Along Width:**

0.750 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.250 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.250 inches

**First Leg Thickness:**

0.060 inches

**Second Leg Thickness:**

0.060 inches

**First Leg Width:**

Between 1.230 inches and 1.280 inches

**First Leg End Width:**

Between 0.860 inches and 0.920 inches

**First Leg Distance From Edge To Hole Center Along Width:**

Between 0.430 inches and 0.460 inches

**First Leg Distance From Edge To Hole Center Along Length:**

Between 0.220 inches and 0.280 inches

**First Leg Style:**

Square and tapered

**First Leg Hole Arrangement Style:**

One hole

**Second Leg Style:**

Square

**Second Leg Hole Arrangement Style:**

Two holes

**Second Leg Relationship To First Leg:**

Identical

**First Leg Angle:**

Between 0.17 radians and 0.23 radians

**Special Features:**

Drawing title clip, actuator - variable nozzle

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams4911/ti6al-4v assn standard all material responses

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A042a0