

View Online at <https://aerobasegroup.com/nsn/5340-01-388-0511>

**First Leg Length:**

2.3800 inches

**Second Leg Length:**

0.8100 inches

**Second Leg Width:**

2.000 inches

**Second Leg End Width:**

1.7600 inches

**First Leg Slot Length:**

0.2600 inches

**First Leg Slot Width:**

Between 0.2200 inches and 0.2250 inches

**Second Leg Distance Between Hole Centers Along Width:**

1.2500 inches

**Second Leg Distance From Edge To Hole Center Along Width:**

0.3800 inches

**Second Leg Distance From Edge To Hole Center Along Length:**

0.2600 inches

**Second Leg Slot Length:**

0.3100 inches

**Second Leg Slot Width:**

0.1730 inches

**First Leg Thickness:**

0.1870 inches

**Second Leg Thickness:**

0.1870 inches

**First Leg Width:**

3.0000 inches

**First Leg Distance Between Hole Centers Along Width:**

2.0000 inches

**First Leg Distance From Edge To Hole Center Along Width:**

0.5000 inches

**First Leg Distance From Edge To Hole Center Along Length:**

0.3600 inches

**First Leg Style:**

Square

**First Leg Hole Arrangement Style:**

2 slots

**Second Leg Style:**

Chamfered ends

**Second Leg Hole Arrangement Style:**

2 slots

**Second Leg Relationship To First Leg:**

Not identical

**First Leg Angle:**

0.0300 radians

**Second Leg Chamfer Angle:**

45.0 degrees

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-200/16 federal specification single material response

**Surface Treatment:**

Chromate

**Surface Treatment Specification:**

Mil-c-5541, cl 3 military specification single treatment response

**Style Designator:**

Angle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A042a0

**Mil-std (military Standard):**

Mil-c-5541 spec.